

---

**ANDELA GLASS PULVERIZER SYSTEM**  
**MODEL GP-05L**  
**(1-2 tons/hr.)**

**MACHINE SPECIFICATIONS**

**Pulverizer**

Machine Input Opening ..... 12" x 12"  
Barrel Diameter and Length ..... 16" x 34"  
Barrel Liner.....Chromium Carbide  
Motor Size..... 7.5 hp  
Solid Steel Shaft Diameter.....2"  
Number of Hammers .....28  
Hammer Type ..... Flailing Arm/Hardened Steel  
Bearing Size.....2"  
Seal Protection ..... 2 Seals at Each Shaft Bearing

**Trommel Screen**

Screen #1..... 24" OD x 2' long, 3/16" screen opening or to specification  
Screen #2..... 24" OD x 2' long, 7/16" screen opening or to specification  
.....Produces 1/8" minus glass sand, 1/8"-3/8" glass aggregate, and 3/8" plus trash  
Screen Type .....Stainless Steel Woven Wire  
Rotating Brushes..... 7" diameter  
Motor Size.....1 hp

**Safety Features**

Protective Guards..... Cover Input Hopper, Drive Unit and Bearings  
Maintenance Features .....Central lubrication Block, External Mount

**Electrical**

Motor Voltage..... 230/460 VAC, 60 HZ, 3 phase  
(Or to customer specifications)

The manufacturer reserves the right to change designs  
and specifications without notice.