

ANDELA GLASS PULVERIZER
MODEL GP-1HD
(10 tons/hr capacity)

MACHINE SPECIFICATIONS

Dimensions

Overall Length	Approx. 64”
Overall Width	Approx. 65”
Machine Input Opening	14” x 14”
Input Chamber Diameter and Length	20” x 34”
Output Chamber Diameter and Length	20” x 44”
Chamber Type	Steel Frame & Heavy Duty Support Stand
Liners	Bolt-in Heavy Duty Abrasion Resistant Steel
Heavy Duty Frame with Spring Action Vibration Mounts	Five (5) Mounts

Drive Componentry

Motor Size	Two (2) 10 hp TEFC
Solid Steel Shaft Diameter	2.5” Dia.
Number of Hammers	44
Hammer Type	Flexible Impactor/Hardened Steel
Bearing Size	2.5” Dia. Heavy Duty
Seal Protection	Two (2) Seals at Each Shaft Bearing

Safety & Maintenance Features

Protective Guards	Cover Input Hopper, Drive Unit and Bearings
Maintenance Access Door	Chamber Inspection
Dust Control Misting System	Pump with Adjustable Spray Nozzle

Electrical

Motor Voltage	230/460 VAC, 60 HZ, 3 phase
---------------------	-----------------------------

The manufacturer reserves the right to change designs
and specifications without notice.