

ANDELA GLASS PULVERIZER
MODEL GP-2HD
20 tons/hr. capacity

MACHINE SPECIFICATIONS

Dimensions

Overall Length	Approx. 88”
Overall Width	Approx. 79”
Infeed Hopper Opening	36” x 36”
Machine Input Opening	20” x 20”
Input Chamber Diameter and Length	30” x 44”
Output Chamber Diameter and Length	30” x 58”
Chamber Type.....	Steel Frame & Heavy Duty Support Stand
Liners	Bolt-in Heavy Duty Abrasion Resistant Steel
Heavy Duty Frame with Vibration Isolation	(5) Mechanical Spring Isolators

Drive Componentry

Motor Size	Two (2) 20 HP TEFC
Solid Steel Shaft Diameter	3” Dia.
Number of Hammers	56
Hammer Type	Flexible Impactor/Hardened Steel
Bearing Size.....	3” Heavy Duty
Seal Protection.....	Two (2) Seals At Each Shaft Bearing

Safety Features

Protective Guards	Cover Input Hopper, Drive Unit and Bearings
Access Doors.....	Hammer and Liner Maintenance

Electrical

Motor Voltage	230/460 VAC, 60 HZ, 3 phase
---------------------	-----------------------------

Weight

Static Weight	7,500 lbs.
---------------------	------------

The manufacturer reserves the right to change designs
and specifications without notice.