

Glass Pulverizer/Screener with Infeed Conveyor

Accepts all types of glass

Produce both glass sand and glass aggregates, separated from larger debris

Infeed Conveyor

Total System: 7 HP 3 phase 240-480V

Environmentally friendly
Reduces waste
Provides cost effective remedy
for environmentally conscious
communities

ANDELA PRODUCTS

493 State Route 28 Richfield Springs, NY 13439 315-858-0055

www.andelaproducts.com info@andelaproducts.com



- Process 1500-2000 pounds of glass per/hour.
- Infeed all types of glass, no precleaning required.
- Produce both a glass sand and glass aggregate, without sharp edges.
- Integrated trommel screen separates out the residue (caps, labels, and corks).
- Compact and integrated unit with Pulverizer, Trommel Screen, and Elec Controls





- Quiet operation
- Simple to operate and maintain
- Reasonably priced
- Industrial strength design
- Cleated rubber conveyor with self cleaning tail pulley
- Big machine features with a small machine



ANDELA GLASS PULVERIZER SYSTEM MODEL GP-MegaMini

Bulk Fed GP-MM Pulverizer with Trommel Screen and Conveyor 1500-2000 lbs. / hour

MACHINE SPECIFICATIONS

Dimensions
Overall Length162"
Overall Width99"
Overall Height
Approx. Shipping Weight
Pulverizer
Machine Input Opening
Barrel Diameter and Length 16" x 34"
Barrel Liner
Motor Size
Solid Steel Shaft Diameter
Number of Hammers
Hammer Type
Bearing Size2" Heavy Duty
Seal Protection 2 Seals at Each Shaft Bearing
Soul From the Earling
Trommel
Screen Barrel Diameter and Length
Rotating Brush
Screen Type
Motor Size
Conveyor
Belt Type 14 Troughing, 3 in. Cleated Rubber Belt, Self-Cleaning Tail Pulley
Motor
1
Safety Features
E-Stop
Protective Guards
Electrical – Control Panel Included Pre-wired to Motors
Motor Voltage230/460V, 60 Hz 3 Phase (Or to Customer Specifications)
Controls
-

The manufacturer reserves the right to change designs and specifications without notice.



Heavy Duty Design Highlights

High quality, low maintenance design for abrasion resistance

Heavy duty construction to outlast competitors

Chromium Carbide Liners last up to 6,000 hours

Produces crushed and/or pulverized glass with no sharp edges.


Two sizes: Glass Sand and Glass Aggregate

Use locally to replace sand or gravel in landscaping, construction, or other applications.



Electrical Control Panel

- **Enclosures** Enclosures are rated per the environment and are NEMA 4 or better. All enclosures are supplied with an emergency stop.
- **Main Disconnect** The main disconnect is provided with fuses or a circuit breaker and has a "Lockout/Tag out" feature.
- **Motor Starters** The motor starters are IEC rated.
- **Branch Circuit Protectors** The Branch circuit protectors are provided with a circuit breaker and a motor overload as an integral part of the unit.
- **Push Buttons** All push buttons are heavy duty dust tight/water tight design.
- **Standards** Built to UL-508 Industrial Standards. Electrical schematics and parts lists are supplied with the unit when the whole system is shipped. Can be CE certified upon request.





Richfield Springs, NY 13439

Tel: 315-858-0055 andelaproducts.com 1/17/2024 CHECKED BY: SCALE 1:40

GP-MM GLASS PULVERIZER-MEGA MINI SYSTEM

ANDELA PRODUCTS

	ISION .	DA*		
ALL EQUIPMENT PAINTED RAL-5015 SKY BLUE, ALL GUARDS AND				
RAILINGS PAINTED RAL-1023 TRAFFIC YELLOW, AND ALL PLATFORMS				

GP-MM PAINTED RAL-9017 TRAFFIC BLACK, UNLESS OTHERWISE NOTED

SHEET 1 OF 1