



Andela

Trommel

Trommel Screener

30" & 48" diameters

6ft–15ft long

1.5 HP–7.5 HP

3 material separations

1 or 2 aggregate sizes

1 oversize / residual

Various Applications

Glass

Compost

Plastics

Rubber

Gravel

Mixed Material

ANDELA PRODUCTS

493 State Route 28
Richfield Springs, NY 13439

Phone: (315) 858-0055

www.andelaproducts.com
info@andelaproducts.com



The Andela Trommel Screen Separator is designed to separate and size aggregate using woven wire mesh or perforated plate.

Our trommels feature direct drive systems flexibly mounted with totally enclosed gear reducers for long lasting performance.

Comes equipped with rotating brushes for cleaning the screens.

Customizable chutes build to customer specification.

- Simple to operate and maintain
- Easy Installation
- Reasonably priced
- Durable
- Totally enclosed with easy access doors
- Single frame construction

ANDELA TROMMEL SEPARATOR
ATROM-101

MACHINE SPECIFICATIONS

Screen Sizes

Screen #130" OD x 3' long
 1/8" or to specification
 Screen #230" OD x 3' long
 3/8" or to specification

Categories of Separation

1/8" minus - glass sand (or to specification)
 1/8" - 3/8" - glass sand/gravel (or to specification)
 3/8" plus - trash

Dimensions

Overall Length Approx. 12'
 Overall Width Approx. 5'
 Screen Barrel Diameter and Length..... 30" x 7 ft
 Screen TypeStainless Steel Woven Wire
 Rotating Brushes.....(2) - 7" diameter
 Maintenance FeaturesCentral lubrication Block, External Mount
 EnclosureComplete Sheet Metal Enclosure
 Hinged Service Door for Screen & Brushes

Drive Componentry

Motor Size(1) 1 1/2 hp
 Direct Drive System Totally Enclosed Gear Reducer
Flexible Mount and Clutch Mechanism

Electrical

Motor Voltage..... 230/460 VAC, 60 HZ, 3 Phase
 Controls Push Button Start/Stop

The manufacturer reserves the right to change designs
 and specifications without notice.