



Andela

TWIN BARREL

Andela GP-2HD

Model:
GP-2HD: 20 TPH

**Designed for High
Capacity Applications**

**Flexible Impact
Hammers**

*Reduces waste
Provides a cost effective remedy
for environmentally conscious
communities*

ANDELA PRODUCTS

493 State Route 28
Richfield Springs, NY 13439

Phone: (315) 858-0055

www.andelaproducts.com
info@andelaproducts.com



- Selective size reduction produces a glass sand, and glass aggregate, while leaving non glass residue in-tact for ease of separation
- Machine design features access doors with bolt in replacement liners and hammers for hassle free maintenance and service
- Generates safe handling glass product with no sharp edges suitable for a variety of
 - Quiet Operation
 - Simple to Operate and Maintain
 - Low Horsepower
 - Reasonably Priced
 - Durable
 - Bolt in Liners and Hammers for Easy Maintenance.
 - Processes whole glass bottles and/or MRF glass

ANDELA GLASS PULVERIZER
MODEL GP-2HD
20 tons/hr. capacity

MACHINE SPECIFICATIONS

Dimensions

Overall Length	Approx. 88”
Overall Width	Approx. 79”
Infeed Hopper Opening	36” x 36”
Machine Input Opening	20” x 20”
Input Chamber Diameter and Length	30” x 44”
Output Chamber Diameter and Length	30” x 58”
Chamber Type.....	Steel Frame & Heavy Duty Support Stand
Liners	Bolt-in Heavy Duty Abrasion Resistant Steel
Heavy Duty Frame with Vibration Isolation	(5) Mechanical Spring Isolators

Drive Componentry

Motor Size	Two (2) 20 HP TEFC
Solid Steel Shaft Diameter	3” Dia.
Number of Hammers	56
Hammer Type	Flexible Impactor/Hardened Steel
Bearing Size.....	3” Heavy Duty
Seal Protection.....	Two (2) Seals At Each Shaft Bearing

Safety Features

Protective Guards	Cover Input Hopper, Drive Unit and Bearings
Access Doors.....	Hammer and Liner Maintenance

Electrical

Motor Voltage	230/460 VAC, 60 HZ, 3 phase
---------------------	-----------------------------

Weight

Static Weight	7,500 lbs.
---------------------	------------

The manufacturer reserves the right to change designs
and specifications without notice.